

SPC RIGID CLICK 3.20 mm / 0.30mm

TECHNICAL SPECIFICATIONS	STANDARD	PRODUCT SPECIFICATIONS
Type of Floorcovering	ISO 10582	HETEROGENEOUS PVC
Overall thickness	EN ISO 24346	3.20 mm
Wear layer thickness	EN ISO 23340	0.30 mm
Total weight	EN ISO 23997	7175 g/m ²
Wear resistance	EN 660-2	Group T
Surface treatment		PUR
Click system		I4F
Class of use	EN ISO 10874	23-31

TECHNICAL PERFORMANCES	STANDARD	PRODUCT PERFORMANCES
Fire classification	EN 13501-1	Bfl-s1
Slip resistance	EN 13893	DS
Slip resistance	DIN 51130	R9
Residual indentation	EN ISO 24343-1	≤0,10 mm
Dimensional stability	EN ISO 23999	≤0,25%
Dimensional stability -Best value measured	EN ISO 23999	0.05%
Castor chair resistance	ISO 4918	PASS
Furniture leg resistance	EN ISO 16581	PASS
Acoustic insulation	EN ISO 717-2	13 dB
Heat insulation	EN ISO 10456	0,25w/(m.K)
Thermal resistance R	EN 12664	0,01 m ² . K/W
Electrostatic performance	EN 1815	< 2 kV
Thermal resistance	EN 12664	0,010m ² .K/W
Light fastness	ISO 105-B02	≥6
Stain resistance	EN ISO 26987	PASS
TVOC after 28 DAYS	ISO 16000	<0.5mg/m ³
DOP number / CE MARKING	EN 14041/2004	19DOP-SPC3.5/0.30-007

