

## SPC RIGID CLICK 3.20 mm / 0.30mm - ACOUSTIC - 4.50 mm

| TECHNICAL SPECIFICATIONS                   | STANDARD       | PRODUCT SPECIFICATIONS    |
|--------------------------------------------|----------------|---------------------------|
| Type of Floorcovering                      | ISO 10582      | HETEROGENEOUS PVC         |
| Overall thickness                          | EN ISO 24346   | 3.20 mm                   |
| Wear layer thickness                       | EN ISO 23340   | 0.30 mm                   |
| Total weight                               | EN ISO 23997   | 7920 g/m <sup>2</sup>     |
| Wear resistance                            | EN 660-2       | Group T                   |
| Surface treatment                          |                | PUR                       |
| Click system                               |                | 14F                       |
| Class of use                               | EN ISO 10874   | 23-31                     |
| Attached IXPE foam for Acoustic Insulation |                | 1.00 mm                   |
| TECHNICAL PERFORMANCES                     | STANDARD       | PRODUCT PERFORMANCES      |
| Fire classification                        | EN 13501-1     | Bfl-s1                    |
| Slip resistance                            | EN 13893       | DS                        |
| Slip resistance                            | DIN 51130      | R9                        |
| Residual indentation                       | EN ISO 24343-1 | ≤0,10 mm                  |
| Dimensional stability                      | EN ISO 23999   | ≤0,25%                    |
| Dimensional stability -Best value measured | EN ISO 23999   | 0.05%                     |
| Castor chair resistance                    | ISO 4918       | PASS                      |
| Furniture leg resistance                   | EN ISO 16581   | PASS                      |
| Acoustic insulation                        | EN ISO 717-2   | 21 dB                     |
| Heat insulation                            | EN ISO 10456   | 0,25w/(m.K)               |
| Thermal resistance R                       | EN 12664       | 0,01 m <sup>2</sup> . K/W |
| Electrostatic performance                  | EN 1815        | < 2 kV                    |
| Thermal resistance                         | EN 12664       | 0,010m <sup>2</sup> .K/W  |
| Light fastness                             | ISO 105-B02    | ≥6                        |
| Stain resistance                           | EN ISO 26987   | PASS                      |
| TVOC after 28 DAYS                         | ISO 16000      | < 0.5mg/m <sup>3</sup>    |
| DOP number / CE MARKING                    | EN 14041/2004  | 19DOP-SPC3.5/0.30-007     |

